



Awning Window


Configurations




Full Awning




Double Awning




Double top Awning




Double bottom Awning



Bottom Awning



Top Awning



Fixed Awning

Minimum/Maximum Sizes

FULL AWNING

- Min 1³1⁴ Max 4⁶3⁰

DOUBLE AWNING

- Min 3⁰1⁶ Max 9⁰3⁰

BOTTOM/TOP AWNING

- Min 1³2⁶ Max 4⁶8⁰

DOUBLE BOTTOM/TOP AWNING

- Min 3⁰2⁶ Max 8⁰6⁰

Egress not possible with awning windows

Available Frame Styles

NO NAIL-ON FIN:

8420T Block Frame

8470T 1-5/8" Narrow Z-Bar (Tuscany only)

8440T 2-1/8" Wide Z-Bar (Tuscany only)

INCLUDES NAIL-ON FIN:

8420T 1-3/8" Nail Fin Setback

8430T 1" Nail Fin Setback with Stucco Key

8440T 1-3/8" Nail Fin Setback, 2" Long Nail Fin

8440T 1-3/8" Nail Fin Setback, 2" Long Nail Fin with optional:

- 3/4" Flat J-channel
- 1" Contoured J-channel
- 2" Brickmold
- Welded Brickmold

NOTE: For engineering approval contact your Milgard representative for any configuration over 40 square feet. Each Milgard Manufacturing plant reserves the right to alter or change sizes and configurations according to location capabilities. Ask your Milgard rep about specialty applications. Windows over 40 square feet shipped open for field glazing. Varies by location.

Not all frame styles available at all Milgard locations. Contact your Milgard Representative for more information.