



Casement Window


Configurations




Full Casement




Single Casement




Fixed Casement



Double Casement



Double bottom Casement



Double Casement/Picture

NOTE: For engineering approval contact your Milgard representative for any configuration over 40 square feet. Each Milgard Manufacturing plant reserves the right to alter or change sizes and configurations according to location capabilities. Ask your Milgard rep about specialty applications. Windows over 40 square feet shipped open for field glazing. Varies by location.

Not all frame styles available at all Milgard locations. Contact your Milgard Representative for more information.

Minimum/Maximum Sizes

FULL CASEMENT

- Min 1⁶1⁰ Max 3⁰5⁰ or 2⁶6⁰

SINGLE CASEMENT

- Min 3⁰1⁶ Max 6⁰5⁰ or 5⁰6⁰

DOUBLE CASEMENT WITH PICTURE

- Min 4⁰1⁶ Max 12⁰6⁰ with 30" vent set
- Maximum vent size is 15 square feet
- Minimum egress for casement is 2¹¹3⁶ or 2⁴4⁰
- 18" height and width required for rotary hardware

FIXED CASEMENT

- Min 1⁶1⁰ Max 6⁰6⁰

Available Frame Styles

NO NAIL-ON FIN:

8520T Block Frame

8570T 1-5/8" Narrow Z-Bar (Tuscany only)

8540T 2-1/8" Wide Z-Bar (Tuscany only)

INCLUDES NAIL-ON FIN:

8520T 1-3/8" Nail Fin Setback

8530T 1" Nail Fin Setback with Stucco Key

8540T 1-3/8" Nail Fin Setback, 2" Long Nail Fin

8540T 1-3/8" Nail Fin Setback, 2" Long Nail Fin with optional:

- 3/4" Flat J-channel
- 1" Contoured J-channel
- 2" Brickmold-style J-channel
- Welded Brickmold