

Performance Ratings



Clearly the best.™

Updated: 8/2014

Window Type	Series	Test		Structural Class	Air Infiltration	Water * Test (PSF)	Min					Max				
		size	bs/vs				Width		Height		bs/vs	Width		Height		bs/vs
Half Vent	8120T 8130T 8140T 8170T	6050	-	LC-PG-40	0.04	6	2	0	1	6	-	6	0	5	0	-
Double Vent		8060	-	HS-LC-30	0.03	6	2	0	1	6		8	0	6	0	24
Double Vent		10050	36	HS-LC-25	0.1	6	3	0	3	0		10	0	5	0	36
Double Vent		13060	48	HS-R-15	0.1	6	3	0	1	6	12	13	0	6	0	48
Half Vent Below		6080	36	LC-PG-25	0.05	3.75/6.75	2	0	3	0		6	0	6	0	36
Half Vent Above		6080	36	LC-PG-25	0.03	3.75	2	0	3	0		6	0	8	0	36
Double Vent Below		10060	-	HS-R-20	0.09	3.75/5.25	4	0	3	0		10	0	6	0	36
Double Vent Above		10060	-	HS-R-20	0.03	3.75/5.25	4	0	3	0		10	0	6	0	36
Double Slider		8125T	6050	-	HS-LC-25	0.06	3.75	2	0	1	6		6	0	5	0
Single Hung	8220T 8230T 8240T 8270T	net 44 X 75	C	H-LC-40	0.04	6	1	6	2	0	12	3	8	6	3	
Single Hung		4080	C	H-LC-35	0.16	6	1	6	2	0	12	4	0	8	0	
Triple Single Hung		9077	C	H-R-20	0.09	4.5	4	6	2	6		9	0	7	7	
Special config - transom over O/O   O/X		6076	C	H-LC-25	0.08	4.5	-	-	-	-	-	6	0	7	6	
Double Hung	8225T	net 44 x 75	C	H-LC-30	0.28	5.25	1	6	2	0	12	3	8	6	3	37.5
Double Hung		4070	C	H-LC-25	0.27	5.25	1	6	2	0	12	4	0	7	0	37.5
Double Double Hung		net 83 x 66	C	H-R-30	0.23	4.5	1	6	2	0	12	6	11	5	6	20
Double Double Hung		-	C	H-LC-30	0.21		3	0	2	0	12	6	0	6	3	37.5
Triple Double Hung		net 108 x 75	C	H-LC-30	0.21		4	6	2	0	12	9	0	6	3	37.5
Picture Window	8320T 8330T 8340T	8060	-	FW-HC-40	0.005	12	1	6	1	6	-	8	0	6	0	-
Octagon		-	-	FW-HC-40	-	12	2	0	2	0	-	6	0	6	0	-
Full Round		-	-	FW-HC-40	-	12	2	6	2	6	-	6	0	6	0	-
1/2 Round		-	-	FW-HC-40	-	12	2	6	1	3	-	8	0	4	0	-



Window Type	Series	Test		Structural Class	Air Infiltration	Water * Test (PSF)	Min					Max				
		size	bs/vs				Width		Height		bs/vs	Width		Height		bs/vs
SGD Transom	8621TR	9050	-	TR-LC25	0.01	6.75	5	0	1	6	-	9	0	5	0	-
SGD Canada	8622	10080	-	LC-PG25	0.1	5.25	5	0	6	8	-	10	0	8	0	-
Inswing - XX	8642T 8662T	net 76 X 95.5	-	SHD-LC25	0.04	3.75	5	0	6	8	-	6	4	8	0	-
Inswing - XO/OX		net 76 X 95.5		SHD-LC25	0.04	3.75	5	0	6	8		6	4	8	0	
Inswing - XXXX		10480		SHD-LC25	0.03	3.75	10	4	6	8		10	4	8	0	
Inswing -OXXO		10480	-	SHD-LC25	0.05	3.75	10	4	6	8	-	10	4	8	0	-
Inswing -X		-	-	-	-	-	2	6	8	0		3	0	8	0	
Inswing - Sidelite		net 24 x 80	-	R PG30	0.17	4.6						2	0	6	8	
Outswing - XX	8643T 8663T	net 76 X 95.5		SHD-LC35	0.07	5.25	5	0	6	8		6	4	8	0	
Outswing - XO/OX		net 76 X 95.5	-	SHD-LC35	0.01	6.75	5	0	6	8	-	6	4	8	0	-
Outswing - XXXX		10480		SHD-LC25	0.13	3.75	10	4	6	8		10	4	8	0	
Outswing - OXXO		10480	-	SHD-LC30	0.1	4.5	10	4	6	8	-	10	4	8	0	-
Outswing - X		-	-	-	-	-	2	6	8	0	-	3	0	8	0	-

\* The water test pressures are done in a controlled environment and performance in the field may vary. Therefore, AAMA requirements should be reduced to 2/3's of the test pressure for field testing.